

Pt100 temperature sensors for special applications in humid conditions up to 150 / 250 °C

High-grade Pt100 resistance sensor
For measuring operations in very humid atmospheric conditions
Operative over a wide range of temperatures

Pt100 temperature sensors for applications in laboratories and medical engineering



Technical data

Accuracy:	Pt100 film resistor, class A*
Protective tube	Stainless steel, diameter 3 mm, length 20 mm
Operative range	-30 to +150 °C
Cable	PFA, length 5 m
Working pressure	maximum 3.0 bar
Protective class	IP69K
ALMEMO® plug	Pt100 with resolution 0.01 K.

Especially suitable for measuring temperatures in autoclaves, sterilizing units, high-temperature steam applications, vacuum applications, and freeze drying units

Variants

Pt100 sensor, cable length = 5 m, ALMEMO® plug

Order no. FPA30K20L0020

Pt100 temperature sensors for industrial applications in air-conditioning / heat cabinets



Technical data

Accuracy:	Pt100 film resistor, class B*
Protective tube	Stainless steel, diameter 4 mm, length 50 mm
Operative range	-100 to +250 °C
Cable	PFA
Protective class	IP68
ALMEMO® plug	Pt100 with resolution 0.01 K.

Especially suitable for measuring temperatures in air-conditioning / heat cabinets with high atmospheric humidity
Operative over a wide range of temperatures

Variants

Pt100 sensor, cable length = 5 m, ALMEMO® plug
Pt100 sensor, cable length = 10 m, ALMEMO® plug

Order no. FPA40ST0050S01KL0050

Order no. FPA40ST0050S01KL0100

* Range of validity see page 07.03