

Digital carbon dioxide sensor FYAD 00 CO2 with grip, integrated atmospheric pressure sensor for automatic atmospheric pressure compensation, and ALMEMO® D6 plug



- Digital CO₂ sensor with integrated signal processor
- All sensor characteristics and adjustment data are stored in the CO₂ sensor itself.
- The unique automatic calibration procedure (without fresh air intake) automatically compensates any natural ageing effects.
- The sensor is very well protected against the effects of pollution by means of replaceable PTFE filter caps. Long-term stability is outstanding.
- Automatic atmospheric pressure compensation is provided for pressure-dependent CO₂ concentrations by means of a digital atmospheric pressure sensor integrated in the grip.
- The relevant ambient parameter, atmospheric pressure, is measured using the same sensor.
- Long-term measuring operations can be performed with an ALMEMO® data logger in sleep mode; this applies only to current device types with sleep delay (180 seconds).
- 2 primary measuring channels (real measurable variables) CO₂ concentration and atmospheric pressure
- Freely selectable measurable variables Two measuring channels are programmed (at our factory). CO₂ concentration, average value (ppm), Atmospheric pressure (mbar, AP, p). Alternatively a further variable can be selected. CO₂ concentration, current value (ppm) The configuration is performed on the ALMEMO® V7 measuring instrument or directly on the PC using the USB adapter cable ZA1919AKUV (see chapter "ALMEMO® Network technology").

General features and accessories, ALMEMO® D6 sensors:
see page 01.08

Technical Data

Digital carbon dioxide (CO ₂) sensor (including A/D converter)		Filter cap	PTFE Diameter 18 mm Length appr. 41 mm
Measuring principle	non-dispersive infrared (NDIR) technology	Sensor connector	Plug connection
Sensor	2-beam infrared measuring cell	Grip	with socket, integrated electronics
Measuring range		Dimensions:	Diameter 20 mm Total length including the sensor 245 mm
FYAD00CO2B10	0 to 10,000 ppm	ALMEMO® connecting cable	fitted cable, 2 meters With ALMEMO® D6 plug
FYAD00CO2B05	0 to 5,000 ppm	Digital atmospheric pressure sensor (integrated in grip)	
Accuracy		Measuring range	700 to 1100 mbar
FYAD 00-CO2B10	±(100 ppm +5 % of measured value)	Accuracy	±2.5 mbar (at 23 °C ±5 K)
FYAD 00-CO2B05	±(50 ppm +3 % of measured value)	ALMEMO® D6 plug	
Nominal conditions	+25 °C, 1013 mbar	Refresh rate	1 second for all four channels
Temperature dependence	typical 2 ppm CO ₂ / K in range 0 to +50 °C	Supply voltage	6 to 13 VDC
Response time	<195 seconds	Current consumption	25 mA
Operative range	-40 to +60 °C / 0 to 95 % RH (non-condensing)		
Measuring interval	Moving average 165 seconds (= 11 current values of 15 sec.)		

Type (including factory test certificate)

Digital CO₂ sensor with grip, fitted cable with ALMEMO® D6 plug, and integrated digital atmospheric pressure sensor

Measuring range 10 000 ppm

Measuring range 5 000 ppm

FYAD00CO2B10

Factory calibration KY96xx carbon dioxide concentration for digital sensor (see chapter Calibration certificates)

Order no.

FYAD00CO2B10

FYAD00CO2B05

Carbon Dioxide Probe FYA600CO2



- Since the gas is supplied by means of free convection, this is especially suitable for climatology measurements.
- Various measuring ranges up to 25%.

Technical Data

Gas:	CO ₂	Power supply:	6.5 to 12VDC from the ALMEMO® device Operation with mains supply unit recommended !
Measuring principle:	IR optics	Current consumpt.	eff. 50mA/ max. 70mA
Measuring ranges:	nominal (% CO ₂): 0 ... 2.5%, 0 ... 10%, 0 ... 25%	Settling time t90:	< 60s
Accuracy:	±2% of final value	Temperature coefficient:	typical -0.4% signal/K
Reproducibility:	±1% of final value	Temperature range:	5 to +40°C
Resolution:	(depending on measuring range) <200ppm at 2.5%	Relative humidity:	0 to 95%, noncondensing
Output:	0 ... 2V on ALMEMO® connector Linearization in ALMEMO® device	Dimensions:	W 96mm x H 36mm x D 64mm
Current output:	referred to GND	Weight:	241g
max. burden (load resist.):	400W	Connecting cable:	1.5m long, ALMEMO® connector

! Operation with the device in SLEEP mode is not possible!
When operating more than one CO₂ probe on a single ALMEMO® device, these CO₂ probes will need their own external power supply ! On request we can offer a wide variety of power supply options to suit your particular measuring setup.

Type

Carbon dioxide sensor including connecting cable 1.5m long for CO₂ measurements in air
(Please specify measuring range !)

Factory calibration KY96xx carbon dioxide concentration for measuring chain (sensor + device) (see chapter Calibration certificates)

Order no.
FYA600CO2