

Accessories for measuring instruments ALMEMO® 2450, 2490, 2590 and output interface ZA 8006 RTA



Rubber safety holster, green
 Rubber safety holster, gray
 including carry strap

Order no.
ZB2490GS1
ZB2490GS2



Vent plug with handle,
 to close unneeded ALMEMO® sockets,
 suitable for ALMEMO 2450, 2490, 2470, 2590, 2690, 202,
 710, 1020, 1030, 1036, output interface RTA3/4

GR2400BAG



Top hat rail mounting

1 battery compartment cap with top hat rail holder fitted,
 including top hat

ZB2490HS



Magnetic fastening

2 pot magnets, including 2 screws
 (for battery compartment cap)

ZB2490MH

Rechargeable batteries



Types

Order no.

Rechargeable battery, 12 V, 1600 mAh, NiMH
 with intelligent high-speed charging
 housed in case 174 x 29 x 137 mm (LxWXH) (without plug
 connections) voltage output via 3-pin socket

ZB5690AP

Connector mains unit, 100 to 240 VAC
 for charging the battery

ZB1212NA10

Connecting cable from battery to ALMEMO® device
 length = 1.5 meters, with ALMEMO® plug
 for ALMEMO® 2450, 2490, 2470, 2590-2/-3S/-4S, 2690

ZA1012AKA

With 3-pin bayonet coupling
 for ALMEMO® 5690, 8590, 8690

ZB5090EKA

With hollow connector
 for ALMEMO® 2890, 6290

ZB2290EKA

General accessories

Batteries and Rechargeable Batteries



Types:

AA battery, 1.5 V

AA NiMH rechargeable battery, 1.2 V, 1600 mA, coded for charging in ALMEMO® unit (e.g. ALMEMO® 2690-8)

Order no.

ZB2000B1

ZB2000A1NM

Mains Adapter



Variants

Order no.

Switching power supply / connector variant 100 to 240 VAC

12 VDC, 2 A ALMEMO® connector e.g. for hand-held devices ALMEMO® 2450, 2490, 2590, 2690, 710, 202

ZA1312NA10

12 VDC, 2 A 3-pin bayonet coupling e.g. for ALMEMO® 5690, 8590, 8690, 8036, 500

ZB1212NA10

12 VDC, 2 A DIN hollow connector for ALMEMO® 2890-9, 6290-7B2

ZB1112NA10

12 VDC, 2 A With free ends

ZB1012NA10

Accessories

Conversion connector for mains-powered devices Euro-plug to US standard (flat-pin)

ZB1000UA

DC Power Supply Cables



Supply cables for DC voltages

- Usage for car and electric fence batteries.
- For instruments that need to be supplied from the car battery.

Variants

Order no.

10 to 30 V DC, electrically isolated, with DIN hollow connector for ALMEMO® 2890-9, 6290-7B2

Output : 12V DC / 1 A (max.)

ZB2590UK

10 to 30 V DC, electrically isolated, with ALMEMO® connector for ALMEMO® 2450, 2490, 2590, 2690-8 710, 202

Output: 12 V DC / 250 mA (max.)

ZA2690UK

Output: 12 V DC / 1 A (max.)

ZA2690UK2

10 to 30VDC, electr. isol., with bayonet coupling for ALMEMO® 8590, 8036, 809

Output: 12VDC/250mA (max.)

ZB3090UK

10 to 30VDC, electr. isol., with bayonet coupling, for ALMEMO® 5690-9, 8690, 500

output: 12V DC / 1.25A (max.)

ZB3090UK2

Adapter cable with universal car connector

ZB1000AKU

New ALMEMO® power supply plug, 9 to 12 VDC, not electr. isolated, with clamp connector for ALMEMO® DC socket on hand-held devices ALMEMO® 2450, 2490, 2590, 2690, 710, 202

Programming 0.2 A

ZA1312FS1

Programming 1 A

ZA1312FS8