

## Capacitive humidity sensor FHA 646 R, miniature sensor



- Compact sensor, extremely small dimensions
- Wide operating temperature range
- Particularly suitable for measuring operations between PCBs,

inside cases, in walls, ceilings, and insulation layers used in the construction industry, and for the protection of listed historic monuments

### Technical data

Operative range	-30 to +100 °C, 5 to 98 % RH	Temperature measuring circuit	
Humidity measuring circuit		Sensor	NTC type N
Measuring range	0 to 100 % RH	Accuracy	-20 to 0 ±0.4 K, 0 to +70 ±0.2 K +70 to +100 ±0.6 K
Sensor	capacitive	Reproducibility	0.1 K
Accuracy	±2 % RH in the range <90 % RH at nominal temperature	Mechanical design	
Reproducibility	<1% RH at nominal temperature	Sensor tube	nickel-plated, 50 mm long, 5 mm Ø
Nominal temperature	+25 ±3 °C	Protective cap	None
Response time T63	approx. 10 seconds at 1 m/s	Cable	High-temperature cable (up to +100 °C), 2 meters long, with ALMEMO® plug (no other lengths available)

- ! The sensor can only be operated by plugging DIRECTLY onto an ALMEMO® device.  
(NOT with extension cables ZA9060VKx or ZA9090VKCx).  
Or, alternatively, the following sensor types can be used. FHAD36RAS up to +100 °C (see page 08.08)  
FHAD46-C2 or FHAD46-C0 Compact design (see page 08.06)

### Accessories

	Order no.
PTFE filter, inside diameter 5 mm suitable for protection against dust, not water-proof	ZB9646SKR
Clamped screw connection with thread adapter for telescopic extension / extension set (maximum 80 °C)	ZV9915KV
Telescopic extension Ø 15 to 24 mm, 330 / 1010 mm	ZV9915TV
Extension set Ø 15 mm, 4 x 255 mm	ZV9915VR3



### Variants

	Order no.
Miniature sensor for temperature / humidity, with fitted high-temperature cable, length 2 meters, with ALMEMO® plug	FHA646R

DAkS or factory calibration KH9xxx temperature, humidity for measuring chain (sensor + device) (see chapter „Calibration certificates“).  
DAkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.