

Infrared measuring technology

Compact infra-red probe head AMiR FIA 844 suitable for all ALMEMO® devices



- Compact inexpensive infra-red probe head for measuring surface temperature
- Other measuring ranges $\ -20$ to $+500\ ^{\circ}\mathrm{C}$
- High optical resolution Measuring spot 11.5 mm at distance 150 mm, in distant field 9:1
- Sturdy stainless steel housing Protection IP65
- Quick and easy to install thanks to screw-fit housing
- Integrated electronics, cable permanently fitted
- Can be connected directly to the ALMEMO[®] device using an ALMEMO[®] connector.





Distance D to target [mm]

Accessories	Order no.
Mounting bracket, rigid	ZR7844FB
Mounting bracket, adjustable	ZR7844JB
Air blower attachment Thread M18x1	ZR7844APM
Variants (including 2 mounting nuts): ALMEMO [®] infra-red probe head Measuring range -20 to +500 °C with permanently fitted cable and ALMEMO [®] connector, Cable length = 1 meter	FIA844
Same as above Cable length = 3 meters	FIA844L3
Factory calibration KI9xxx temperature for sensor (see chapter Calibration certificates)	TIA044L3


Infrared measuring technology

Technical data

Temperature range	-20 to +500 °C
Spectral sensitivity	8 to 14 μm
Optical resolution (90 % energy)	13:1 (11.5 mm at 150 mm distance), distant field 9:1
Accuracy	± 1.5 % of measured value or ± 2 K (whichever value is higher) ± 3.5 K for measured values <0 °C
Reproducibility	± 0.5 % of measured value or ± 1 K (whichever value is higher)
Nominal conditions	23 °C ±5 K, Emissivity 0.95
Temperature resolution	0.1 K
Response time	150 ms (95 %)
Emissivity	0.95, fixed setting
Voltage supply	via ALMEMO® connector (12 VDC)
Protection	IP65
Ambient temperature	-10 to +70 °C
Storage temperature	-20 to +85 °C
Relative atmospheric humidity	10 to 95 % non-condensing
Housing	Stainless steel
Dimensions	Length 94 mm Thread M18x1
Connecting cable	permanently fitted, 1 or 3 meters, -30 to +105 °C including ALMEMO [®] connector, programmed
Weight	approx. 160 g (1-meter cable)

Mounting bracket Order no. ZR7844FB





Mounting bracket, adjustable Order no. ZR7844JB

Air blower attachment Thread M18x1 Order no. ZR7844APM



