



Pt100 Type HS High Temperature Precision Thermometers

Precision resistance thermometer model eXacal Pt100HS. With protective sheath of gas-tight ceramic and handmade 100 Ohm ceramic detector.

- ✓ Temperature range: **0°C to 850°C**
- ✓ stable high temperature thermometer with good calibration capability
- ✓ **Protective sheath made of gastight ceramic**
- ✓ **configurable**
In our thermometer configurator you can individually configure the thermometer according to many parameters.
- ✓ **small measurement uncertainties with DAkkS calibration certificate**
The thermometer can be calibrated at fixed temperature points with smaller measurement uncertainties.

Calibration

eXacal thermometers are calibrated in our own DAkkS calibration laboratory. The DAkkS accreditation ensures that all calibrations are traceable to national and international standards. The calibration of eXacal resistance thermometers is carried out at ITS-90 fixed points. It is also possible to carry out calibrations according to the comparison method in liquid baths and calibration furnaces. The measurement uncertainty is calculated from many components. The largest contributions are reproducibility, ITS-90 function, self-heating and hysteresis.

- ✓ Small measurement uncertainties with DAkkS calibration certificate
- ✓ Temperature fixed points up to aluminium freezing point 660,323 °C
- ✓ ITS-90 standard thermometer for comparison calibration

Range	Fixed Point	Uncertainty
0,01°C	Water	6mK
29,7646°C	Gallium	6mK
156,5985°C	Indium	10mK
231,928°C	Tin	11mK
419,527°C	Zinc	21mK
660,323°C	Aluminium	25mk 150mK @ 850°C

The given measurement uncertainties correspond to k=2, include an ITS-90 function and are given for the respective range.

Technical data

Model	eXacal Pt100HS
Temperature range	0 °C to 850 °C
Nominal resistance	Pt100 (100 Ohm)
typical annual drift	2,5mk
Connection type	Four-wire
Connecting cable	temperature resistant – very low EMF stranded wires from own production
Connection	depending on configuration
Sheath material	gas-tight ceramic
Thermometer wire	Platinum
Dimensions	
Handle	∅20mm x 100mm
diameter	6mm
Length	depending on configuration
Connection cable	depending on configuration
Detector	
R0	100 Ohm ± 0,05 Ohm
Alpha	0,003850 ± 0,000005
Standard	IEC 60751:2008
tolerance	individual calibration
length	25mm
recommended measuring current	1mA
Self-heating	4mK
DAkkS Calibration	
Fixed point calibration	6 mK to 25 mK
Comparison calibration	15 mK to 150 mK

Further information:
www.exacal.de

